





Cerritos Elementary School, Cerritos, CA


When it comes to manufacturing hollow metal frames, Stiles offers more profiles, more elevations, and the service you'd expect from the world's leading built-to-order hollow metal manufacturer.

- Door and Window Frames
- Over 20 Standard Profiles
- Fire Rated Frames to 3 HR Rating
- Square, Radius, Arched, Gothic, Curved and More
- Steel, Stainless Steel and Bronze
- Welded, KD, Adjustable, Kerf & Thermal Break
- Factory Primed or Finish Painted
- Available via Quick Ship for FAST Delivery

Section Contents General Frame Construction F-1.0 **Profiles** Typical Jamb & Sill Profiles F-2.0 - 2.1 Frame Welding F-3.0 **Elevations** Frame Elevations F-4.0 - 4.2 **Custom Frame Elevations** F-4.3 Panel Types + Installation F-5.0 F-6.0 **Custom KD Drywall Frames** F-7.0 Adjust-A-Frame™ F-8.0 Seal-Tek™ Frames **Double Egress Frames** F-9.0 **Pocket Frames** F-10.0 Frame Anchor Types F-11.0 - 11.1

Built to Order.™

Notes






General Frame Construction

Construction


Gauge	18, 16, 14, & 12
Material	 Cold Rolled A-60 and G-90 Galvanized 304 and 316 Stainless Steel
Corners	Machine Mitered
Construction Options (STD)NAAMM/HMMA 861: SDI100, HMMA 860:	Face and Soffit Welded Face Welded or Knockdown Full Welded
Hinge Reinforcement	7 GA X 1-1/4" X 10"
Strike Reinforcement	12 GA or equivalent # threads
Closer Reinforcement	12 GA

All Other 12 GA Reinforcement 16, 14, 12 GA Anchors Cold Rolled, Galvanized or Stainless Steel 16, 14, 12 GA Floor Clip Cold Rolled, Galvanized or Stainless Steel Primer Alkyd (Gray), EPA Approved Sprayed Asphalt Coating Sound Deadening Inside of Jambs if requested Fire Rating See Fire Rated Section See Finish Options, Finish Options **General Section** Stainless Steel See Stainless Section for finish

Minimum Frame Dimensions




Frame Nomenclature





Jamb & Sill Profiles









Jamb, Mullion & Sill Profiles





Available via Quick Ship See Quick Ship Section















Shadow Line Frame



Shadow Line Frame



Stiles Custom Metal Inc 1885 Kinser Road Ceres CA USA 95307 T 209 538 3667

F 209 538 2776


E sales@stilesdoor.com

www.stilesdoor.com







WELDED MULLION




CUT-OFF STOP




MITERED + WELDED




MITERED + FACE WELDED



MITERED + FULL WELD



MITERED + KNOCKDOWN



Stiles Custom Metal Inc 1885 Kinser Road Ceres CA USA 95307 T 209 538 3667


F 209 538 2776

E sales@stilesdoor.com



Frame Elevations






Quick Ship 10-DAY

Quick Ship 10-DAY



Frame Elevations









Frame Elevations




Available via Quick Ship: See Quick Ship Section

Multiple Opening Frames









Quick Ship 10-DAY


Single Opening Frames



23
SINGLE LITE
SQUARE FRAMES








Stiles Custom Metal Inc 1885 Kinser Road Ceres CA USA 95307 T 209 538 3667 F 209 538 2776

E sales@stilesdoor.com



Custom Frame Elevations




Stiles Custom Metal Inc 1885 Kinser Road Ceres CA USA 95307 T 209 538 3667 F 209 538 2776


E sales@stilesdoor.com

www.stilesdoor.com





Hollow Metal Panel Installation





Sandwich Panel Installation









Custom KD Drywall Frames






Available via Quick Ship: See Quick Ship Section







OPPOSITE VIEWS OF CORNER MITRE




Drywall frames are designed for quick installation after the walls are in place including drywall. Frame members are shipped unassembled for field assembly and installation.



Install drywall before frame.



Push head into place, interlock jambs to head and pivot into place. Bend tabs over.




Place spreader at bottom to insure proper width. Fasten Bottom anchors to wall. Adjust pressure anchors to plumb frame.



$\textbf{Split-A-Frame}^{\scriptscriptstyle{\mathsf{TM}}}$







Specifications

Gauge	16 or 14 GA
Material	 Cold Rolled A-60 Galvanized
Fire Rating	Up to 1-1/2 HR

*SPECIFY WALL THICKNESS

Stiles Custom Metal Inc 1885 Kinser Road Ceres CA USA 95307 T 209 538 3667

F 209 538 2776

E sales@stilesdoor.com

www.stilesdoor.com







Available via 10-Day Quick Ship: See Quick Ship Section

Seal-Tek At A Glance

Effectively Seals:

- Smoke
- Noise
- Weather

Fire Tested

■ Seal-Tek design many be incorporated into any of our labeled assemblies.

Applications


- Stairwells
- Corridor Entrances
- Computer Rooms
- Equipment Rooms
- Pharmaceutical Labs
- Any Interior or Exterior Location

Construction

■ Manufactured in our factory, either welded or KD. Frame is made from 16 GA material. Kerf type weather strip is fully (and easily) replaceable.

Kerf Seal

■ UL10C listed, available in bronze, white, black, gray, and beige. Seal is installed on the job after finish paint.






Double Egress Frames

Available via Quick Ship: See Quick Ship Section




Stiles Model No. FDE


HEAD SECTIONS




STANDARD JAMB SECTIONS



WALL POCKET JAMB SECTIONS





Head Construction

Gauge 16, 14, or 12 GA

Cased open with applied stop or two-piece welded in middle

F 209 538 2776







Available via 10-Day Quick Ship: See Quick Ship Section *Frame only

