




Security Steel Door Pair



SAMPLE ELEVATION

For additional elevations, see [Doors > Elevations](#)

Fire Rated Door Options

SIZE	FIRE RATING	MATERIAL	DOOR TYPE	CONSTRUCTION
102 X 120	3/4 Hour	12 GA @ Security Door / 14 Gauge	Stainless Steel Stiffened Core	Max. 24 X 24 Listed Louver
	1 Hour	16 Gauge	Stainless Steel, Honeycomb Core	10" Min. Bottom Rail
	1-1/2 Hour	18 Gauge	Stainless Steel, Temperature Rise Core	6" Min. Stile & Rail (1, 1-1/2, 3 HR)
	3 Hour		Stainless Steel, Polystyrene Core	3-3/8" Min. Stile & Rail (3/4 HR)
			Edge Welded	Glass Size per Glass Manufacturer
			Open Seam	Astragal Required
				Cladding

NOTE: Above door data varies depending on specific design criteria

Fire Rated Glass & Glazing Criteria

GLASS TYPE	THICKNESS	MAX WIDTH	MAX HEIGHT	MAX SQ IN	GLASS BRAND
3/4 Hour Fire Rated Doors with Glass					
Wire Glass	.25"	30"	90"	2,019	Multiple
Wire Glass (Glazed with intumescent tape)	.25"	34"	84"	2,856	Multiple
Ceramic Glass	.187	36"	89"	3,205	FireLite®
Laminated Glass	.625" - 1.37"	87.625"	87.625"	3,855	Pyrobel®
Gel-Filled Glass	.75"	124.25"	124.25"	4,952	SuperLite®
1 Hour Fire Rated Doors with Glass					
Ceramic Glass	.187	36"	89"	3,204	FireLite®
Laminated Glass	1" - 1.875"	87.625"	87.625"	3,855	Pyrobel®
Gel-Filled Glass	1.125"	124.25"	124.25"	4,952	SuperLite®
1-1/2 Hour Fire Rated Doors with Glass					
Ceramic Glass	.187"	36"	56.5"	2,034	FireLite®
Laminated Glass	1.375" - 2.125"	36"	61"	2,196	Pyrobel®
Gel-Filled Glass	1.5"	124"	124"	4,876	SuperLite®
3 Hour Doors with Glass					
Ceramic Glass	.187"	12"	33"	100	FireLite®

For additional glass data, see [Fire Rated Glazing Criteria](#)

All Stiles Fire Rated assemblies are built-to-order to your exact specifications. For assistance with design, labeling requirements and multiple integrated features, contact factory.

Stiles®

Steel Door + Window Systems

© 2010 Stiles Custom Metal, Inc. 0710

Stiles Custom Metal Inc
1885 Kinser Road
Ceres CA USA 95307

T 209 / 538-3667
F 209 / 538-2776

www.stilesdoor.com